




Rev No	Revision note	Date	Signature	Checked
A/0				



Recommended P.C. Board Hole Layout

NOTES:
SPECIFICATION
 Current Rating: 1.0Ampereper Contact
 Contact Resistance: 20Milliohms Max
 Insulation Resistance: 500Megohms Min
 Dielectric Withstanding Voltage: 500V AC(for 1 minute)
 Operation Temperature: -40 °C~+105 °C

Material
 Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: Glass Filled Polyester(UL94V-0)
 Standard: Nylon-6T

3230-XX R XX XS12

NO. of Pins	Contact Plating	Color Insulator
10=10P 14=14P 16=16P 20=20P 24=24P 26=26P 30=30P 34=34P 40=40P 44=44P 50=50P 60=60P	G0=Gold Flash G1=3u" Gold G2=5u" Gold G3=10u" Gold G4=15u" Gold G5=30u" Gold S0=Gold Flash/Tin SN=Tin	B=Black W=White U=Blue R=Red Y=Yellow G=Grey

THIS DRAWING IS A CONTROLLED DOCUMENT

DWN	JACK	DATE	OCT 05 2006
CHK	MIKE	DATE	OCT 05 2006
APPD	PETER	DATE	OCT 05 2006

TOLERANCES UNLESS OTHERWISE SPECIFIED

0 P.L.C.	±	—
1 P.L.C.	±	0.20
3 P.L.C.	±	0.25
4 P.L.C.	±	0.30

ANGLES ± 3°

CAGE CODE 00871 FILE PATH

YTCO YTCO TECHNOLOGY
 HTTP://WWW.YTCO.CO

TITLE: 1.27mm Ejector Header, RightAngle DIP

PART NO. 3230-XXRXXXS12

DRAWING NO. YT-3230R1

SHEET 1 OF 1 REV A